

SECTION 3 - Voice and Data Cables

E&J

Services Limited

CW 1308B - internal/external telephone cable 0.5mm diameter solid copper conductor pvc insulated, insulated earth wire, PETP taped, tinned copper drainwire, aluminium taped moisture barrier, black LSF outer sheath.

10 pair + earth, 1Km and 500 metre reels or cut to length
20 pair + earth, 1Km and 500 metre reels or cut to length
50 pair + earth, 1Km and 500 metre reels or cut to length
100 pair + earth, 1Km and 500 metre reels or cut to length

Order Ref.
C 166
C 167
C 168
C 169



CW 1128 external telephone cables - multipair, 0.5mm solid plain copper conductor, pvc insulated, jel filled, black polyethylene outer sheath. Suitable for installation in ducts or directly buried in suitably prepared ground.

5 pair, 1,000 & 500 metre drums or cut to length
10 pair, 1,000 & 500 metre drums or cut to length
20 pair, 1,000 & 500 metre drums or cut to length
50 pair, 500 metre drums or cut to length
100 pair, 500 metre drums or cut to length

Order Ref.
C 140
C 141
C 142
C 144
C 145

CW1128/1179 jel filled and screened external telephone cable.

20 pair, 500m reels or cut to length
100 pair, 500m reels or cut to length

Order Ref
C 158R
C 160R

CW1128/1198 jel filled and steel wire armoured (SWA) external telephone cable.

5 pair, 100,200 & 500m reels or cut to length
10 pair, 100,200 & 500m reels or cut to length
20 pair, 100,200 & 500m reels or cut to length
50 pair, 100,200 & 500m reels or cut to length
100 pair, 500m reels or cut to length

Order Ref
C 151R
C 152R
C 153R
C 154R
C 155R

CW1128/1252 jel filled cable incorporating separate steel support wire for aerial applications in fig 8 configuration.

10 pair, 500m reels or cut to length
20 pair, 500m reels or cut to length
50 pair, 500m reels or cut to length
100 pair, 500m reels or cut to length

Order Ref
C 147R
C 148R
C 149R
C 150R

All CW1308B and CW1128 type cables can be cut to length, to nearest multiple of 50 metres.
No cutting charge.

EXPORT ENQUIRIES WELCOME - 01733 311 592