

## SECTION 3 - Voice and Data Cables

**CW 1044 - functional earth wire - plain copper conductor, cream pvc sheath, supplied on 100 metre reels.**

1.5mm  
2.5mm  
4.0mm  
6.0mm  
10.0mm  
16.0mm

Order Ref.  
C 500  
C 501  
ASK  
ASK  
C 502  
ASK

**Dropwire to CW 247 & CW 1378 - 2 core, 2 pair, 3 pair and 4 pair cable, 0.5mm solid plain copper conductor, pvc insulated, polyethylene outer sheath. The cables incorporate steel strength members and are therefore self-supporting (not dropwire 6).**

Dropwire no. 6, 2 core, to CW 247, 100 & 200 metre reels  
Dropwire no. 10, 2 pair, to CW 1378, 200 & 350 metre reels  
Dropwire no. 11, 3 pair, to CW 1378, 200 metre reels  
Dropwire no. 14, 4 pair, to CW 1378, 200 metre reels  
See Section 6 for dropwire clamps and brackets.

Order Ref.  
C 180  
C 181  
C 182  
C 183

**FCC flat line cordage, stranded tinsel conductor, pvc insulated and over-sheathed. Flat profile for under-carpet installation or for use in lead manufacture**

4 way black, 500m reels  
4 way grey, 500m reels  
4 way white, 500m reels  
6 way black, 500m reels  
6 way grey, 500m reels  
6 way white, 500m reels  
8 way black, 500m reels  
8 way grey, 500m reels  
8 way white, 500m reels

*Shorter reels available if required*

Order Ref  
C 134F4B  
C 134F4G  
C 134F4W  
C 135F6B  
C 135F6G  
C 135F6W  
C 136F8B  
C 136F8G  
C 136F8W

