

## SECTION 4 - Security Cables and Connectors

**E&J**

Services Limited

**Alarm cables - unscreened 7/0.2mm tinned copper conductor, pvc insulated, white pvc outer sheath . Maximum voltage 50V r.m.s. maximum current per core 1 amp. To BS 4737.**

4 core, 100 metre reels  
6 core, 100 metre reels  
8 core, 100 metre reels  
12 core, 100 metre reels

Order Ref.

C 266  
C 264  
C 262  
C 260

**Alarm cables -screened 7/0.2mm tinned copper conductor, pvc insulated, overall aluminium foil screen, white pvc outer sheath. Voltage & current as per unscreened.**

4 core, 100 metre reels  
6 core, 100 metre reels  
8 core, 100 metre reels  
12 core, 100 metre reels

Order Ref.

C 271  
C 270  
C 269  
C 268

**Alarm Cables LSF - 7/0.2mm, tinned copper conductor, pvc insulated, white LSF outer sheath.**

4 core, 100 metre reels  
6 core, 100 metre reels  
8 core, 100 metre reels  
12 core, 100 metre reels

Order Ref.

C 267  
C 265  
C 263  
C 265

*If you require either screened or unscreened cables in longer lengths or different sheath colours, please contact our sales department on 01733-311592.*

**Alarm cables - external 7/0.2mm, tinned copper conductor, pvc insulated, black polyethylene or polypropylene outer sheath. These cables are suitable for use in ducts or directly buried in prepared ground.**

6 core direct burial foil screened, 500 metre reels or cut to length  
12 core direct burial foil screened, 500 metre reels or cut to length

Order Ref.

C 296PP  
C 290PP

6 core duct grade unscreened, 500 metre reels or cut to length  
12 core duct grade unscreened, 500 metre reels or cut to length  
8 core duct grade unscreened, 500 metre reels or cut to length

ASK

ASK

C 262BPE

**TCCA alarm cable – 7/0.2mm tinned copper coated aluminium (TCCA), white pvc sheath, 100 metre reels unless stated otherwise**

6 core black, 100 metre reel  
6 core black, 200 metre reel  
6 core white, 100 metre reel  
8 core white, 100 metre reel

Order Ref.

C 275B1  
C 275B2  
C 275W1  
C 274W1



**PRIORITY FAX LINE - 01733 344 775**