

SECTION 4 - Security Cables and Connectors

E&J

Services Limited

75 ohm co-ax cable - used for CCTV and TV distribution.

RG 59 - c/u version has plain copper 1/0.58mm diameter centre conductor, solid dielectric, plain copper braid screen to Mil C-17, pvc outer sheath. RG 59 c/u PE is suitable for external use, including direct burial in suitably prepared ground and the LSF version is the low smoke and fume internal cable.

RG 59 c/u, black, 100 metres
RG 59 c/u, black, 200 metres
RG 59 c/u, black, 500 metres
RG 59 c/u, PE, black, 250 metres
RG 59 LSF, black, 500 metres
RG 59 LSF, black, 200 metres
RG59c/u LSF, black, 100 metres

Order Ref.
C 211B1
C 211B2
C 211B5
C 212BPER
C 213LSF5
C 213LS52
C 213LSF1

RG 59 - b/u version has copper clad steel 1/0.58mm diameter centre conductor, solid dielectric, plain copper braid screen (80/0.10mm) pvc outer sheath.

RG 59 b/u, black, 100 metres
RG 59 b/u, black, 200 metres
RG59b/u LSF, black, 100 metres

Order Ref.
C 210B1
C 210B2
C 210B1LSF1

URM 70 - plain stranded copper conductor (7/0.19mm) solid dielectric, plain copper braid screen with 94% coverage, pvc outer sheath. Limited fire hazard version available in LSF.

URM 70, LSF, black, 500 metres

Order Ref.
C 216

Co-ax 12 - 0.75mm diameter plain copper centre conductor, solid dielectric, plain copper foil and copper braid screen, polyethylene outer sheath. This is an external cable which can be directly buried in suitably prepared ground.

Co-ax 12 PE, black, 500 metres

Order Ref.
C 214R

RG 6 - plain copper conductor, 1mm diameter, airspaced dielectric, double screened - foil and braid, black pvc outer sheath. Available in white or brown sheath to order, traditionally used for satellite t.v. applications.

RG 6, black, 100 metres
RG 6, black, 250 metres

Order Ref.
C235B1
C235BR

RG 179 LSF - a miniature 75 ohm co-ax, overall diameter 2.5mm. Stranded (7/0.12mm) or solid conductor, polyethylene dielectric, braid screen and lsf outer sheath in black.

RG 179, stranded conductor, black lsf sheath, 100 metres
RG 179, solid conductor, black lsf sheath, 100 metres

Order Ref.
C 233STR
C 233



ORDER BEFORE 4pm - FOR SAME DAY DESPATCH