SECTION 5 - Cables

Belden equivalent cables - continued

9728 LSF, 4 pair, individual foil screen pairs, 24 awg low smoke and fume sheath, 500 metre reels	Order Ref. C 449
9729 LSF, 2 pair individual foil screen, low capacitance 24 awg, low smoke and fume sheath, 500 metre reels	C 450
9730 LSF, 3 pair, individual foil screen pairs, 24 awg low smoke and fume sheath, 500 metre reels	C 451
9829 LSF, 2 pair overall foil and braid screen, 24 awg low smoke and fume sheath, 500 metre reels	C 455
9841 LSF, 1 pair foil and braid screen, 24 awg low smoke and fume sheath, 500 metre reels	C 461
9842 LSF, 2 pair overall foil and braid screen, 24 awg low smoke and fume sheath, 500 metre reels	C 462
9842 PE, 2 pair overall foil and braid screen, 24 awg	C 462PE

The Belden cables listed represent those which we are most often asked to supply. If you

pe sheath for external/direct burial application, 500 metre reels

have a requirement for a cable which is not listed we will be pleased to quote. Cables can be supplied on alternative length reels to those shown if required.

Many Belden equivalent cables stocked on 500m reels but can be cut to length (within reason) at no extra charge. Please contact the Sales Office for further details and availability.

Any of the above LSF cables can be supplied in PE, LSOH or armoured versions, Subject to minimum order quantity (MOQ). Please contact sales office with your requirements.







e-mail: sales@eandjservices.co.uk