
SECTION 9 - Cable Manufacture




3183-AG 3183-Y 3184-Y 2182-Y 2192-Y

Heat Resisting Flexible







Mad	le in E	ngland	*
4 W	y D	6 Way D	•
6 Core '	D' sha	pe Corda	age
4 Core "	D' sha	pe Corda	ae

PVC Flexible Mains Cords & Cables

CONDUCTOR:	Plain annealed copper conductor
SPECIFICATION:	Manufactured to BS 6500
INSULATION:	PVC
VOLTAGE RATING:	300/500V
CORES:	2 Core Oval 2,3,4,5 Core Round
SIZES:	0.5mm to 2.5mm
SHEATH COLOURS:	Black, Grey, White or Orange

Heat Resisting (85°C or 105°C) Security / Alarm / Cables

CONDUCTOR:	7/0.20mm - Tinned Annealed copper
SPECIFICATION:	Manufactured to BS 4737 (section 3.30)
INSULATION:	PVC / POLY
VOLTAGE:	Maximum operating voltage 50 r.m.s
MAKE - UP	4,6,8,& 12 cores
SHEATH COLOURS:	WHITE / BROWN / BLACK

Flexible Figure '8' Speaker Cables

CONDUCTOR:	Plain annealed copper conductor
SPECIFICATION:	Manufactured To BS6141
INSULATION:	PVC
VOLTAGE RATING:	300/300V
SIZES:	7/0.20 13/0.20 28/0.15 42/0.15 24/0.20 32/0.20 42/0.20 79.020
COLOURS:	White, Grey, Black, with tracers

Telephone Cordage Flat FCC68 SBS1620

CONDUCTOR:	7/0.15 Tinned annealed copper	
SPECIFICATION:	FCC 68 and SBS 1620	
INSULATION:	PVC or Polypropylene	
MAKE - UP	4, 6 and 8 cores Conductors are laid up in a parallel Fashion with a pvc outer sheath With a flat cross section	
SHEATH COLOURS:	Grey / Ivory / White / Black	

Telephone Cordage 'D' Shape

CONDUCTOR:	Duplex/Simlex or 7/0.15 Tinned	
SPECIFICATION:	CW 1311 - CW1630 - CW 1690	
INSULATION:	PVC or Polypropylene	
MAKE - UP	4, 6 and 8 core Conductors are laid up in a parallel Fashion with a pvc outer sheath With a 'D' Shape cross section	
SHEATH COLOURS:	Grey / Ivory / White / Black	