

SECTION 3 - Voice and Data Cables

CW 1308B - internal/external telephone cable 0.5mm diameter solid copper conductor pvc insulated, insulated earth wire, PETP taped, tinned copper drainwire, aluminium taped moisture barrier, black LSF outer sheath.

10 pair + earth, 1Km and 500 metre reels or cut to length
20 pair + earth, 1Km and 500 metre reels or cut to length
50 pair + earth, 1Km and 500 metre reels or cut to length
100 pair + earth, 1Km and 500 metre reels or cut to length
200 pair + earth, 1Km and 500 metre reels or cut to length
320 pair + earth, 1Km and 500 metre reels or cut to length

Order Ref.
C 099AGC
C 099CGC
C 099DGC
C 099D1GC
C 099D2
C 099D3



CW 1128 external telephone cables - multipair, 0.5mm solid plain copper conductor, pvc insulated, jel filled, black polyethylene outer sheath. Suitable for installation in ducts or directly buried in suitably prepared ground.

5 pair, 1,000 & 500 metre drums or cut to length
10 pair, 1,000 & 500 metre drums or cut to length
20 pair, 1,000 & 500 metre drums or cut to length
30 pair, 500 metre drums or cut to length
50 pair, 500 metre drums or cut to length
100 pair, 500 metre drums or cut to length

Order Ref.
C 019
C 020
C 021
C 022
C 023
C 024

CW 1128 2 pair available to order, also 0.9mm conductor versions of above are available to order, subject to minimum order quantity. Please check with sales office (01733-311592) when you have a requirement.

PRIORITY ORDER LINE - 01733-311592