

SECTION 4 - Security Cables & Connectors

Alarm cables - unscreened 7/0.20mm tinned copper conductor, pvc insulated, white pvc outer sheath . Maximum voltage 50V r.m.s. maximum current per core 1 amp. To BS 4737.

4 core, 100 metre reels
6 core, 100 metre reels
8 core, 100 metre reels
12 core, 100 metre reels

Order Ref.
C 0584
C0586
C 0588
C 05812

Alarm cables -screened 7/0.20mm tinned copper conductor, pvc insulated, overall aluminium foil screen, white pvc outer sheath. Voltage & current as per unscreened.

4 core, 100 metre reels
6 core, 100 metre reels
8 core, 100 metre reels
12 core, 100 metre reels

Order Ref.
C 0594
C0596
C0598
C05912

If you require either screened or unscreened cables in longer lengths or different sheath colours, please contact our sales department on 01733-311592.

Alarm cables - external 7/0.20mm, tinned copper conductor, pvc insulated, black polyethylene or polypropylene outer sheath. These cables are suitable for use in ducts or directly buried in prepared ground.

6 core direct burial foil screened, 500 metre reels or cut to length
12 core direct burial foil screened, 500 metre reels or cut to length

Order Ref.
C 0606SPP5
C 06012SPP5

6 core duct grade foil screened, 500 metre reels or cut to length
12 core duct grade foil screened, 500 metre reels or cut to length

C 0606SPE
C 06012SPE

6 core duct grade unscreened, 500 metre reels or cut to length
12 core duct grade unscreened, 500 metre reels or cut to length
8 core duct grade unscreened, 500 metre reels or cut to length

C 0606E
C 06012E
C 0608E

Limited fire hazard cables - 7/0.20mm, tinned copper conductor, pvc insulated, white LSF outer sheath.

6 core, 100 metre reels
8 core, 100 metre reels
12 core, 100 metre reels

Order Ref.
C 0616
C 0618
C 05812L

