

SECTION 4 - Security Cables & Connectors

75 ohm co-ax cable - used for CCTV and TV distribution.

RG 59 - c/u version has plain copper 1/0.58mm diameter centre conductor, solid dielectric, plain copper braid screen to Mil C-17, pvc outer sheath. RG 59 c/u PE is suitable for external use, including direct burial in suitably prepared ground and the LSF version is the low smoke and fume internal cable.

RG 59 c/u, black, 100 metres
RG 59 c/u, black, 200 metres
RG 59 c/u, black, 250 metres
RG 59 c/u, black, 500 metres
RG 59 c/u, white, 100 metres
RG 59 c/u, white, 200 metres
RG 59 c/u, white, 250 metres
RG 59 c/u, white, 500 metres
RG 59 c/u, PE, black, 250 metres
RG 59 LSF, black, 500 metres
RG 59 LSF, black, 200 metres

Order Ref.

C 039B1
C 039B2
C 039B25
C 039B5
C 040W1
C 040W2
C 040W25
C 040W5
C 041B25
C041LSF5
C 041LSF2

RG 59 - b/u version has copper clad steel 1/0.58mm diameter centre conductor, solid dielectric, plain copper braid screen (80/0.10mm) pvc outer sheath.

RG 59 b/u, black, 100 metres
RG 59 b/u, black, 200 metres
RG 59 b/u, black, 500 metres
RG 59 b/u, white, 100 metres

Order Ref.

C 039C1
C 039C2
C 039C5
C 039CW1

RG 59 MULTICORES - available to special order in up to 10 core versions. Price and delivery lead time available from sales office 01773-311592.

URM 70 - plain stranded copper conductor (7/0.19mm) solid dielectric, plain copper braid screen with 94% coverage, pvc outer sheath. Limited fire hazard version available in LSF.

URM 70, black, 100 metres
URM 70, black, 200 metres
URM 70, black, 250 metres
URM 70, black, 500 metres
URM 70, white, 100 metres
URM 70, white, 500 metres
URM 70, LSF, black, 500 metres
URM 70, LSF, black 200 metres

Order Ref.

C 043B1
C 043B2
C 043B25
C 043B5
C 044W1
C 044W5
C 044A
C 044L20

Co-ax 12 - 0.75mm diameter plain copper centre conductor, solid dielectric, plain copper foil and copper braid screen, polyethylene outer sheath. This is an external cable which can be directly buried in suitably prepared ground.

Co-ax 12 PE, black, 100 metres
Co-ax 12 PE, black, 250 metres
Co-ax 12 PE, black, 500 metres

Order Ref.

C 042B1
C 042B25
C 042B5

