

## SECTION 4 - Security Cables & Connectors

**RG 6 - plain copper conductor, 1mm diameter, airspaced dielectric, double screened - foil and braid, black pvc outer sheath. Available in white or brown sheath to order, traditionally used for satellite t.v. applications.**

RG 6, black, 100 metres  
RG 6, black, 250 metres

Order Ref.  
C0521  
C05225

**CTS 100 - plain copper conductor, 1mm diameter, airspaced dielectric, copper foil and copper braid screened, black pvc or LSF (low smoke and fume) outer sheath. This cable is manufactured by many companies and is known by other references e.g. TR 100, QC 100, SM 100A, H 109F, however all the cables share virtually identical physical and electrical characteristics and are therefore inter-changeable.**

CTS 100, black, 100 metres  
CTS 100, black, 250 metres  
CTS 100, black, 500 metres  
CTS100, white, 100 metres

Order Ref.  
C 045A1  
C 045A  
C 045A5  
C 045W1

CTS 100, LSF, black 100 metres  
CTS 100 LSF, black, 250 metres  
CTS 100 LSF, black, 500 metres

C 045L1  
C 045  
C 0455

CTS 100 PE, black, 500 metres

C 045PE

CTF 100 foam filled dielectric (Sat. tv use)

C 045QF

CT 100 RBS, black, direct burial, 500 metres

C 045RBS

**RG 11 - stranded tinned copper conductor, 7/0.41mm, solid dielectric, plain copper braid screen, black pvc outer sheath.**

RG 11 LSF a/u, black lsf sheath, 500 metres

Order Ref.  
C 044

**RG 11 SWA (steel wire armoured) - available to special order, call 01733 - 311592 for price and delivery.**

**CT 125 - solid plain copper conductor, 1.25mm diameter, airspaced dielectric, plain copper foil and plain copper braid screened, pvc, tsf, pe or RBS outer sheath. Suitable for internal, external and direct burial applications respectively. Exact equivalents from other manufacturers include QC 125, TR 125 and CTS 125.**

CT 125 pvc, black, 500 metres  
CT 125 pvc, black, 250 metres

Order Ref.  
C072A5  
C072A2

CT 125 PE, black, 1000 metres  
CT 125 PE, black, 500 metres  
CT 125 PE, black, 250 metres

C072P1  
C072P5  
C072P2

CT 125 RBS, green, 1000 metres  
CT 125 RBS, green, 500 metres  
CT 125 RBS, green, 250 metres

C072R10  
C072R5  
C072R2

CT 125 LSF, black, 250 metres  
CT 125 LSF, black, 500 metres

C 072L2  
C 072L5

