

SECTION 4 - Security Cables & Connectors

CT 167 - solid plain copper conductor, 1.67mm diameter, airspaced dielectric, plain copper foil and plain copper braid screened, pe or RBS outer sheath, suitable for external and direct burial purposes. Equivalents from other manufacturers would include TR 165.

CT 167 PE, black, 500 metres
CT 167 RBS, black, 500 metres
CT 167 LSF, black, 250 metres

Order Ref.
C 0735
C 0735R
C 0735LSF

CT 233 - solid plain copper conductor, 2.33mm diameter, airspaced dielectric, plain copper foil and plain copper braid screened, pe sheath suitable for external and direct burial applications in suitably prepared ground.

CT 233 PE, black, 250 metres

Order Ref.
C 074

RG 179 LSF - a miniature 75 ohm co-ax., overall diameter 2.5mm. Stranded conductor, 7/0.12mm, polyethylene dielectric, braid screen and lsf outer sheath in black.

RG 179, black lsf sheath, 100 metres

Order Ref.
C 075S

RG 179 LSF - a miniature 75 ohm co-ax., overall diameter 2.5mm. Solid conductor, polyethylene dielectric, braid screen and lsf outer sheath in black.

RG 179, black lsf sheath, solid conductor, 100 metres

Order Ref.
C 075

Mini-RG 59 - a miniature 75 ohm co-ax, nominal overall diameter 3.8mm. Solid conductor, polyethylene dielectric, braid screen and pvc outer sheath in black or white.

Mini-RG, white, 500 metres
Mini-RG 59, black, 500 metres

Order Ref.
C 041MINW
C 041MIN

TV Downlead - commercial grade low-loss, airspaced cable with plain copper 1mm solid conductor, plain copper braid screen and pvc outer sheath.

TV co-ax, brown, 100 metre reels
TV co-ax, brown, 250 metre reels

Order Ref.
C 0771
C 0772

